

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings of claims in the application.

Listing of Claims:

1. (currently amended) A photosensitive resin laminate comprising ~~at least~~ a support, an adhesive layer and a photosensitive resin layer, wherein the photosensitive resin laminate shows a total light transmission of not less than 60% and wherein the photosensitive resin layer has a thickness of not less than 500 µm.
2. (currently amended) The photosensitive resin laminate of claim 1, wherein the photosensitive resin layer has a ~~thickness of not less than 500 µm and a Shore D hardness of not less than 50^o 50.~~
3. (original) The photosensitive resin laminate of claim 1, wherein the photosensitive resin layer has an absorbance at 400 nm - 600 nm of not more than 0.3.
4. (original) The photosensitive resin laminate of claim 1, wherein the photosensitive resin layer has a scattering rate of not more than 25%.
5. (original) The photosensitive resin laminate of claim 1, wherein the photosensitive resin layer has a turbidity of not more than 3.5.
6. (original) The photosensitive resin laminates of claim 1, wherein the photosensitive resin layer contains a hydroxylamine derivative.

7. (original) A plate for a signboard comprising the photosensitive resin laminate of claim 1.

8. (original) A signboard having a relief, which comprises the photosensitive resin laminate of claim 1, wherein the photosensitive resin layer has a thickness of not less than 500 μm and is formed at least on the support via the adhesive layer, and a coating layer having ~~an ultraviolet~~ a transmission at 400 nm of not more than 50% on its surface.

9. (original) A signboard having a relief, which comprises the photosensitive resin laminate of claim 1, and a layer having an image laminated on a side of the support.

10. (original) The signboard of claim 9, wherein the layer having the image is directly printed on the back of the support.

11. (currently amended) A photosensitive resin laminate comprising ~~at least~~ a support, an adhesive layer and a photosensitive resin layer, which laminate satisfying the following formula (1):

$$\{(A-B)/A\} \times 100 \leq 15 \quad (1)$$

wherein A is a total light transmission (%) of the support and B is a total light transmission (%) of the photosensitive resin laminate and wherein the photosensitive resin layer has a thickness of not less than 500 μm .

12. (currently amended) The photosensitive resin laminate of claim 11, wherein the photosensitive resin layer has a ~~thickness of not less than 500 μm and~~ a Shore D hardness of not less than 50° 50.

13. (original) The photosensitive resin laminate of claim 11, wherein the photosensitive resin layer has an absorbance at 400nm - 600 nm of not more than 0.3.

14. (original) The photosensitive resin laminate of claim 11, wherein the photosensitive resin layer has a scattering rate of not more than 25%.

15. (original) The photosensitive resin laminate of claim 11, wherein the photosensitive resin layer has a turbidity of not more than 3.5.

16. (original) The photosensitive resin laminates of claim 11, wherein the photosensitive resin layer contains a hydroxylamine derivative.

17. (original) A plate for a signboard comprising the photosensitive resin laminate of claim 11.

18. (currently amended) A signboard having a relief, which comprises the photosensitive resin laminate of claim 11, wherein the photosensitive resin layer has a thickness of not less than 500 μm and is formed at least on the support via the adhesive layer, and a coating layer having ~~an ultraviolet~~ a transmission at 400 nm of not more than 50% on its surface.

19. (original) A signboard having a relief, which comprises the photosensitive resin laminate of claim 11, and a layer having an image laminated on a side of the support.

20. (original) The signboard of claim 19, wherein the layer having the image is directly printed on the back of the support.